

俊科[®] SHX 同轴固定衰减器 (Coaxial Fixed Attenuators) 50 ohm

型号(Model Number): SMA25
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 25W
峰值功率(Peak Power): 1KW
(5μs pulse, 2.5% duty cycle)
外型尺寸(Dimensions):
Ø63×47mm
重量(Weight): 115g
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40		
SMA25-XX-8	DC-8	±0.4	±0.5	±0.5	±0.5	1.20	SMA
SMA25-XX-12.4	DC-12.4	±0.5	±0.8	±0.8	±0.8	1.25	
SMA25-XX-18	DC-18	±1.0	±1.0	±1.0	±1.0	1.30	SMA, 2.92mm
SMA25-XX-26.5	DC-26.5	±1.2	±1.2	±1.2	±1.2	1.35	

※ XX refer to attenuation value in dB



型号(Model Number): DTS50GA
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 50W
峰值功率(Peak Power): 1KW
(5μs pulse, 5% duty cycle)
外型尺寸(Dimensions):
Ø63×71mm
重量(Weight): 120g
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40		
DTS50GA-XX-12.4	DC-12.4	±0.5	±0.8	±0.8	±0.8	1.20	SMA, 3.5mm, 2.92mm
DTS50GA-XX-18	DC-18	±1.0	±1.0	±1.0	±1.0	1.25	
DTS50GA-XX-26.5	DC-26.5	-1.0/+2.5	-1.0/+1.5	-1.0/+1.5	-1.0/+1.5	1.30	

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		40	50	60			
DTS50GA-XX-12.4	DC-12.4	±0.8	-1.0/+0.7	-1.0/+0.5		1.20	SMA, 3.5mm, 2.92mm
DTS50GA-XX-18	DC-18	±1.0	±1.0	-1.0/+0.75		1.25	
DTS50GA-XX-26.5	DC-26.5	-1.0/+1.5	±1.0	±1.0		1.30	

※ XX refer to attenuation value in dB



型号(Model Number): SMK50-26.5(-F)
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 50W
峰值功率(Peak Power): 1KW
(5μs pulse, 5% duty cycle)
外型尺寸(Dimensions):
Ø63×71mm
F: 141×122×145mm
重量(Weight): 120g
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40		
SMK50-XX-18	DC-18	±1.0	±1.0	±0.8	±1.0	1.25	2.92mm
SMK50-XX-26.5	DC-26.5	-1.0/+2.5	-1.0/+1.5	-1.0/+1.5	±1.0	1.30	

※ XX refer to attenuation value in dB



型号(Model Number): TS2
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 2W
峰值功率(Peak Power): 0.5KW
(5μs pulse, 0.4% duty cycle)
外型尺寸(Dimensions):
A: Ø20×70mm
B: Ø20×60mm
重量(Weight): A: 65g B: 65g
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		1-9	10	20	30		
TS2-XX-1	DC-1	±0.4	±0.4	±0.4	±0.4	1.10	A: N, SMA, TNC, BNC B: N, SMA, TNC,
TS2-XX-2	DC-2	±0.4	±0.4	±0.4	±0.5	1.15	
TS2-XX-3	DC-3	±0.4	±0.5	±0.5	±0.8	1.20	
TS2-XX-4	DC-4	±0.4	±0.5	±0.5	±0.8	1.25	
TS2-XX-6	DC-6	±0.5	±0.5	±0.5	±0.6	1.30	N, SMA, TNC

※ XX表示衰减值, 40dB针对A型
(XX refer to attenuation value in dB, 40dB corresponding A type.)



* 外型尺寸公差±5% (Dimensions Tolerance ±5%)

**若非特别说明,外形尺寸和技术指标对应N型连接器(Dimensions and specifications refer to connector type N unless otherwise specified.)

***可按客户要求订制特殊规格衰减量和精度(Custom designs available for other special attenuation value & accuracy.)

俊科[®] SHX 同轴固定衰减器 (Coaxial Fixed Attenuators) 50 ohm

型号(Model Number): TS2G, TS2GA, TS2GH

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 2W

峰值功率(Peak Power): 0.5KW(5μs pulse, 0.4% duty cycle)

温度范围(Tem.Range): -55°C~+125°C



型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)										最大驻波比 Max VSWR		连接器形式 Connector Type	外形尺寸 Dimensions (mm)	重量 Weight (g)
		1-9	10	20	30	40	50	60	70	80	90	普通型 Normal	精密型 Precise			
TS2G-XX-8-A	DC-8	±0.5	±0.4	±0.4	±0.5	±0.6	/	/	/	/	/	1.30	/	N,TNC,SMA	Ø20×77	80
TS2G-XX-12.4-A	DC-12.4	±0.7	±0.7	±0.7	±0.7	±0.75	/	/	/	/	/	1.35	/			
TS2G-XX-18-A	DC-18	-0.6/+1.2	±1.0	±1.2	±1.2	±1.2	/	/	/	/	/	1.40	/			
TS2G-XX-8-B(C)	DC-8	±0.5	±0.4	±0.4	±0.5	±0.6	±0.6	/	/	/	/	1.30	1.20	N,TNC,SMA	B:Ø20×60 C:Ø20×63.5	B:65 C:65
TS2G-XX-12.4-B(C)	DC-12.4	±0.7	±0.7	±0.7	±0.7	±0.75	±0.75	/	/	/	/	1.35	1.25			
TS2G-XX-18-B(C)	DC-18	-0.4/+1.2	±1.0	±1.2	±1.2	±1.2	±1.2	/	/	/	/	1.40	1.30			
TS2GA-XX-8-A(B)	DC-8	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	/	/	/	/	/	/	1.20	/	A:N B:N,TNC	A:Ø20×73 B:Ø20×60	A:80 B:65
TS2GA-XX-12.4-A(B)	DC-12.4	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	/	/	/	/	/	/	1.25	/			
TS2GA-XX-18-A(B)	DC-18	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	/	/	/	/	/	/	1.30	/			
TS2GA-XX-8-C	DC-8	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	±0.6	±0.6	/	/	/	/	1.20	/	N,TNC	Ø20×63.5	65
TS2GA-XX-12.4-C	DC-12.4	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	±0.75	±0.75	/	/	/	/	1.25	/			
TS2GA-XX-18-C	DC-18	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	±1.2	±1.2	/	/	/	/	1.30	/			
TS2GH-XX-8	DC-8	/	/	/	/	±0.75	±0.75	±0.8	±1.0	±1.0	±1.5	1.25	1.20	N,TNC	Ø20×69	70
TS2GH-XX-12.4	DC-12.4	/	/	/	/	±1.25	±1.25	±1.0	±1.2	±1.2	±2.0	1.30	1.25			
TS2GH-XX-18	DC-18	/	/	/	/	±1.5	±1.5	±1.5	±1.5	±2.0	±2.5	1.35	1.30			

※ XX refer to attenuation value in dB

型号(Model Number): TS5

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 5W

峰值功率(Peak Power): 0.5KW

(5μs pulse, 1% duty cycle)

外形尺寸(Dimensions):

A: Ø20×70mm

B: Ø20×60mm

重量(Weight): A: 65g B: 65g

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)						最大驻波比 Max VSWR	连接器形式 Connector Type
		1-9	10	20	30	40			
TS5-XX-1	DC-1	±0.4	±0.4	±0.4	±0.4	±0.4		1.10	A:N,SMA,TNC, BNC B:N,SMA,TNC,
TS5-XX-2	DC-2	±0.4	±0.4	±0.4	±0.5	±0.5		1.15	
TS5-XX-3	DC-3	±0.4	±0.5	±0.5	±0.6	±0.6		1.20	
TS5-XX-4	DC-4	±0.4	±0.5	±0.5	±0.6	±0.6		1.25	N,SMA,TNC
TS5-XX-6	DC-6	±0.5	±0.5	±0.5	±0.6	±0.7		1.30	

※ XX表示衰减值, 40dB针对A型

(XX refer to attenuation value in dB, 40dB corresponding A type.)



型号(Model Number): TS5G, TS5GA, TS5GH

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 5W

峰值功率(Peak Power): 0.5KW(5μs pulse, 1% duty cycle)

温度范围(Tem.Range): -55°C~+125°C



型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)										最大驻波比 Max VSWR		连接器形式 Connector Type	外形尺寸 Dimensions (mm)	重量 Weight (g)
		1-9	10	20	30	40	50	60	70	80	90	普通型 Normal	精密型 Precise			
TS5G-XX-8-A	DC-8	±0.5	±0.4	±0.4	±0.5	±0.6	/	/	/	/	/	1.30	/	N,TNC,SMA	Ø20×77	80
TS5G-XX-12.4-A	DC-12.4	±0.7	±0.7	±0.7	±0.7	±0.75	/	/	/	/	/	1.35	/			
TS5G-XX-18-A	DC-18	-0.6/+1.2	±1.0	±1.2	±1.2	±1.2	/	/	/	/	/	1.40	/			
TS5G-XX-8-B(C)	DC-8	±0.5	±0.4	±0.4	±0.5	±0.6	±0.6	/	/	/	/	1.30	1.20	N,TNC,SMA	B:Ø20×60 C:Ø20×63.5	B:65 C:65
TS5G-XX-12.4-B(C)	DC-12.4	±0.7	±0.7	±0.7	±0.7	±0.75	±0.75	/	/	/	/	1.35	1.25			
TS5G-XX-18-B(C)	DC-18	-0.4/+1.2	±1.0	±1.2	±1.2	±1.2	±1.2	/	/	/	/	1.40	1.30			
TS5GA-XX-8-A(B)	DC-8	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	/	/	/	/	/	/	1.20	/	A:N B:N,TNC	A:Ø20×73 B:Ø20×60	A:80 B:65
TS5GA-XX-12.4-A(B)	DC-12.4	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	/	/	/	/	/	/	1.25	/			
TS5GA-XX-18-A(B)	DC-18	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	/	/	/	/	/	/	1.30	/			
TS5GA-XX-8-C	DC-8	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	±0.6	±0.6	/	/	/	/	1.20	/	N,TNC	Ø20×63.5	65
TS5GA-XX-12.4-C	DC-12.4	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	±0.75	±0.75	/	/	/	/	1.25	/			
TS5GA-XX-18-C	DC-18	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	-0.3/+0.6	±1.2	±1.2	/	/	/	/	1.30	/			
TS5GH-XX-8	DC-8	/	/	/	/	±0.75	±0.75	±0.8	±1.0	±1.0	±1.5	1.25	1.20	N,TNC	Ø20×69	70
TS5GH-XX-12.4	DC-12.4	/	/	/	/	±1.25	±1.25	±1.0	±1.2	±1.2	±2.0	1.30	1.25			
TS5GH-XX-18	DC-18	/	/	/	/	±1.5	±1.5	±1.5	±1.5	±2.0	±2.5	1.35	1.30			

※ XX refer to attenuation value in dB

* 外形尺寸公差±5% (Dimensions Tolerance ±5%)

**若非特别说明,外形尺寸和技术指标对应N型连接器(Dimensions and specifications refer to connector type N unless otherwise specified.)

***可按客户要求订制特殊规格衰减量和精度(Custom designs available for other special attenuation value & accuracy.)

俊科[®] SHX 同轴固定衰减器 (Coaxial Fixed Attenuators) 50 ohm

型号(Model Number): DTS10
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 10W
峰值功率(Peak Power): 1KW
(5μs pulse, 1% duty cycle)
外型尺寸(Dimensions):
Ø38×83mm B: Ø30×83mm
重量(Weight): 120g B: 105g
温度范围(Tem. Range):
-55°C ~ +125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		1-9	10	20	30	40		
DTS10-XX-1	DC-1	±0.4	±0.4	±0.4	±0.5	±0.5	1.10	N, SMA, TNC, BNC
DTS10-XX-2	DC-2	±0.4	±0.4	±0.5	±0.5	±0.6	1.15	
DTS10-XX-3	DC-3	±0.4	±0.5	±0.6	±0.6	±0.8	1.20	
DTS10-XX-4	DC-4	±0.5	±0.6	±0.6	±0.6	±0.8	1.25	
DTS10-XX-6	DC-6	±0.5	±0.6	±0.6	±0.6	±0.8	1.30	N, SMA, TNC

※ XX refer to attenuation value in dB



型号(Model Number): DTS10G, DTS10GA, DTS10GH
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 10W
峰值功率(Peak Power): 1KW(5μs pulse, 1% duty cycle)
温度范围(Tem. Range): -55°C ~ +125°C



型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)							最大驻波比 Max VSWR	连接器形式 Connector Type	外形尺寸 Dimensions (mm)	重量 Weight (g)
		3,6	10	20	30	40	50	60				
DTS10G-XX-8	DC-8	±0.5	±0.5	±0.5	±0.5	±0.6	/	/	1.30	N,TNC, SMA	Ø38×77	80
DTS10G-XX-12.4	DC-12.4	±0.8	±0.8	±0.8	±0.8	±0.8	/	/	1.35			
DTS10G-XX-18	DC-18	/	±1.0	±1.0	±1.2	±1.2	/	/	1.40(SMA:1.45)			

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)							最大驻波比 Max VSWR		连接器形式 Connector Type	外形尺寸 Dimensions (mm)	重量 Weight (g)
		1-9	10	20	30	40	50	60	普通型 Normal	精密型 Precise			
DTS10GA-XX-8	DC-8	±0.5	±0.5	±0.5	±0.5	±0.5	/	/	1.20	1.15	N	Ø38×83	115
DTS10GA-XX-12.4	DC-12.4	-0.4/+0.8	-0.4/+0.8	-0.4/+0.8	-0.4/+0.8	-0.4/+0.8	/	/	1.25	1.20			
DTS10GA-XX-18	DC-18	-0.4/+0.8	-0.4/+0.8	-0.4/+0.8	-0.4/+1.0	-0.4/+1.0	/	/	1.30	1.30			

DTS10GH-XX-8-A	DC-8	/	±0.5	±0.5	±0.5	±0.7	±1.0	±1.0	1.25	/	N,TNC, SMA	Ø38×90	140
DTS10GH-XX-12.4-A	DC-12.4	/	±0.8	±0.8	±0.8	±0.8	±1.2	±1.2	1.35	/			
DTS10GH-XX-18-A	DC-18	/	±1.0	±1.0	±1.0	±1.0	/	/	1.40 1.45(SMA)	/			
DTS10GH-XX-8-B	DC-8	/	±0.5	±0.5	±0.5	±0.7	±1.0	±1.0	1.25	/	N,TNC, SMA	Ø38×89	100
DTS10GH-XX-12.4-B	DC-12.4	/	±0.8	±0.8	±0.8	±0.8	±1.2	±1.2	1.35	/			
DTS10GH-XX-18-B	DC-18	/	±1.0	±1.0	±1.0	±1.0	/	/	1.40 1.45(SMA)	/			

※ XX refer to attenuation value in dB

型号(Model Number): DTS25
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 25W
峰值功率(Peak Power): 1KW
(5μs pulse, 2.5% duty cycle)
外型尺寸(Dimensions):
A: Ø38×83mm B: Ø45×110mm
C: Ø30×83mm
重量(Weight):
A: 120g B: 220g C: 105g
温度范围(Tem. Range):
-55°C ~ +125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)						最大驻波比 Max VSWR	连接器形式 Connector Type
		1-9	10	20	30	40	50		
DTS25-XX-1	DC-1	±0.4	±0.4	±0.4	±0.5	±0.5	±0.75	1.10	N,SMA,TNC, BNC,7/16
DTS25-XX-2	DC-2	±0.4	±0.4	±0.5	±0.5	±0.75	±1.0	1.15	
DTS25-XX-3	DC-3	±0.4	±0.5	±0.6	±0.6	±1.0	±1.2	1.20	
DTS25-XX-4	DC-4	±0.5	±0.6	±0.6	±0.6	±1.0	±1.5	1.25	
DTS25-XX-6	DC-6	±0.5	±0.6	±0.75	±0.75	±1.0	±1.5	1.30	

※ XX refer to attenuation value in dB



型号(Model Number): DTS25G-D
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 25W
峰值功率(Peak Power): 1KW
(5μs pulse, 2.5% duty cycle)
外型尺寸(Dimensions):
Ø63×73mm
重量(Weight): 160g
温度范围(Tem. Range):
-55°C ~ +125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度				最大驻波比 Max VSWR	连接器形式 Connector Type
		Attenuation Value & Accuracy(dB)					
		10	20	30	40		
DTS25G-XX-18-D	DC-18	±1.0	±1.0	±1.0	±1.0	1.30	N,TNC

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度			最大驻波比 Max VSWR	连接器形式 Connector Type
		Attenuation Value & Accuracy(dB)				
		50	60	70		
DTS25G-XX-18-D	DC-18	-1.0/+1.5	±1.0	-1.0/+1.2	1.30	N,TNC

※ XX refer to attenuation value in dB



* 外型尺寸公差±5% (Dimensions Tolerance ±5%)

**若非特别说明,外形尺寸和技术指标对应N型连接器(Dimensions and specifications refer to connector type N unless otherwise specified.)

***可按客户要求订制特殊规格衰减量和精度(Custom designs available for other special attenuation value & accuracy.)

俊科[®] SHX 同轴固定衰减器 (Coaxial Fixed Attenuators) 50 ohm

型号(Model Number): DTS25G,DTS25GH

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 25W

峰值功率(Peak Power): 1KW(5μs pulse,2.5% duty cycle)

温度范围(Tem.Range): -55°C~+125°C



型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)						最大驻波比 Max VSWR	连接器形式 Connector Type	外形尺寸 Dimensions (mm)	重量 Weight (g)
		10	20	30	40	50	60				
DTS25G-XX-8	DC-8	±0.5	±0.5	±0.5	±0.75	/	/	1.30	N,TNC, SMA	A:Ø38×77 B:Ø45×77 D:Ø30×77	A:115 B:220 D:100
DTS25G-XX-12.4	DC-12.4	±0.8	±0.8	±0.8	±1.0	/	/	1.35			
DTS25G-XX-18	DC-18	±1.0	±1.0	±1.0	±1.25	/	/	1.40 1.45(SMA)			
DTS25GH-XX-8	DC-8	±0.5	±0.5	±0.5	±0.6	±1.0	±1.0	1.25	N,TNC, SMA	A:Ø38×90 B:Ø45×90 C:Ø30×90	A:140 B:220 C:125
DTS25GH-XX-12.4	DC-12.4	±1.0	±1.0	±1.0	±1.0	±1.2	±1.2	1.35			
DTS25GH-XX-18	DC-18	±1.0	±1.0	±1.0	±1.0	/	/	1.40 1.45(SMA)			

※ XX refer to attenuation value in dB

型号(Model Number): DTS30

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 30W

峰值功率(Peak Power): 1KW

(5μs pulse,3% duty cycle)

外型尺寸(Dimensions):

Ø48×118mm

重量(Weight): 400g

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40			
DTS30-XX-1	DC-1	±0.3	±0.3	±0.4	±0.5		1.10	N,SMA, 7/16,BNC
DTS30-XX-2	DC-2	±0.4	±0.4	±0.5	±0.6		1.15	
DTS30-XX-3	DC-3	±0.5	±0.5	±0.6	±0.7		1.20	
DTS30-XX-4	DC-4	±0.5	±0.6	±0.7	±0.8		1.25	
DTS30-XX-6	DC-6	±0.8	±0.8	±0.8	±0.8		1.30	N,SMA

※ XX refer to attenuation value in dB



型号(Model Number): DTS30G

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 30W

峰值功率(Peak Power): 5KW

(5μs pulse,0.6% duty cycle)

外型尺寸(Dimensions):

A:126×38×38mm

B:112×38×38mm


重量(Weight): A:265g;B:245g

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		3.6	10	20	30	40		
DTS30G-XX-2.5	DC-2.5	±0.3	±0.3	±0.3	±0.3	±0.3	1.10	N
DTS30G-XX-4	DC-4	±0.3	±0.3	±0.3	±0.4	±0.5	1.15	
DTS30G-XX-6	DC-6	±0.4	±0.4	±0.4	±0.5	±0.75	1.20	
DTS30G-XX-8-B	DC-8	±0.6	±0.6	±0.6	±0.75	±1.0	1.30	
DTS30G-XX-10-B	DC-10	±0.7	±0.8	±0.8	±1.0	±1.2	1.35	

※ XX refer to attenuation value in dB, Type A is waterproof.



型号(Model Number): DTS50-A

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 50W

峰值功率(Peak Power): 10KW

(5μs pulse,0.5% duty cycle)

外型尺寸(Dimensions):

130×60×60mm

重量(Weight): 510g

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		1-9	10	20	30	40		
DTS50-XX-1-A	DC-1	±0.4	±0.3	±0.3	±0.3	±0.3	1.15	N,SMA,7/16 ,TNC,BNC
DTS50-XX-2-A	DC-2	±0.5	±0.4	±0.4	±0.5	±0.5	1.20	
DTS50-XX-3-A	DC-3	±0.8	±0.5	±0.5	±0.6	±0.6	1.30	
DTS50-XX-4-A	DC-4	±0.75	±0.75	±0.75	±0.75	±0.75	1.35	

※ XX refer to attenuation value in dB



* 外型尺寸公差±5% (Dimensions Tolerance ±5%)

**若非特别说明,外形尺寸和技术指标对应N型连接器(Dimensions and specifications refer to connector type N unless otherwise specified.)

***可按客户要求订制特殊规格衰减量和精度(Custom designs available for other special attenuation value & accuracy.)

俊科[®] SHX 同轴固定衰减器 (Coaxial Fixed Attenuators) 50 ohm

型号(Model Number): DTS50G

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 50W

峰值功率(Peak Power): 5KW

(5μs pulse, 1% duty cycle)

外型尺寸(Dimensions):

A: Ø63×112mm B: Ø38×112mm

C: Ø45×112mm D: Ø30×112mm

E: 68×70×112mm

重量(Weight): A: 325g B: 245g

C: 270g D: 230g E: 585g

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		3,6	10	20	30	40		
DTS50G-XX-2.5	DC-2.5	±0.3	±0.3	±0.3	±0.3	±0.3	1.10	N,7/16, SMA
DTS50G-XX-3	DC-3	±0.3	±0.3	±0.3	±0.4	±0.5	1.15	
DTS50G-XX-4	DC-4	±0.3	±0.3	±0.3	±0.4	±0.5	1.15	
DTS50G-XX-6	DC-6	±0.4	±0.4	±0.4	±0.5	±0.75	1.20	
DTS50G-XX-8	DC-8	±0.6	±0.6	±0.6	±0.75	±1.0	1.30	N,7/16
DTS50G-XX-10	DC-10	±0.7	±0.8	±0.8	±1.0	±1.2	1.35	

※ XX refer to attenuation value in dB



型号(Model Number): DDT550

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 50W

峰值功率(Peak Power): 10KW

(5μs pulse, 0.5% duty cycle)

外型尺寸(Dimensions):

122×60×30.5mm

重量(Weight): 360g

温度范围(Tem.Range):

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		3,6	10	20	30	40		
DDT550-XX-1	DC-1	±0.4	±0.3	±0.3	±0.3	±0.3	1.15	N,7/16
DDT550-XX-2	DC-2	±0.5	±0.4	±0.4	±0.5	±0.5	1.20	
DDT550-XX-3	DC-3	±0.6	±0.5	±0.5	±0.6	±0.6	1.30	
DDT550-XX-4	DC-4	±0.75	±0.75	±0.75	±0.75	±0.75	1.35	

※ XX refer to attenuation value in dB



型号(Model Number): DTS50GH

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 50W

峰值功率(Peak Power): 1KW(5μs pulse, 5% duty cycle)

温度范围(Tem.Range): -55°C~+125°C



型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)								最大驻波比 Max VSWR	连接器形式 Connector Type	外型尺寸 Dimensions (mm)	重量 Weight (g)
		3	6	10	20	30	40	50	60				
DTS50GH-XX-12.4	DC-12.4	/	/	±1.2	±1.2	±1.25	±1.25	/	/	1.30 1.35(SMA)	N,TNC, SMA	A: Ø38×132 B: Ø45×132	A: 210 B: 230
DTS50GH-XX-18	DC-18	/	/	±1.5	±1.25	±1.5	±1.5	/	/	1.35 1.45(SMA)			
DTS50GH-C(E)-XX-8	DC-8	±0.8	±1.0	±1.0	±1.0	±0.8	±1.0	/	/	1.20	N,TNC, SMA	C: Ø63×91 E: 68×70×91	C: 330 E: 500
DTS50GH-C(E)-XX-12.4	DC-12.4	±0.8	±1.0	±1.0	±1.2	±0.8	±1.2	/	/	1.30			
DTS50GH-C(E)-XX-18	DC-18	-1.0/+1.5	-1.0/+1.5	-1.0/+1.5	-1.0/+1.5	±1.0	-1.0/+1.5	/	/	1.35			
DTS50GH-D-XX-8	DC-8	/	/	±0.4	±0.6	±0.5	±0.5	-1.0/+0.5	-1.0/+0.5	1.20	N,TNC, SMA	Ø63×97	230
DTS50GH-D-XX-12.4	DC-12.4	/	/	±0.5	±0.6	±0.8	±0.8	-1.0/+0.75	-1.0/+0.75	1.25			
DTS50GH-D-XX-18	DC-18	/	/	±1.0	±1.0	±1.0	±1.0	±1.0	±1.0	1.30			

※ XX refer to attenuation value in dB

型号(Model Number): WDT550

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 50W

峰值功率(Peak Power): 5KW

(5μs pulse, 1% duty cycle)

外型尺寸(Dimensions):

A: 112×130×75mm

重量(Weight): A: 815g

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		3/6	10	20	30	40		
WDT550-XX-2.5	DC-2.5	±0.3	±0.3	±0.3	±0.3	±0.3	1.10	N,7/16
WDT550-XX-4	DC-4	±0.3	±0.3	±0.3	±0.4	±0.5	1.20	
WDT550-XX-6	DC-6	±0.4	±0.4	±0.4	±0.5	±0.75	1.30	
WDT550-XX-8	DC-8	±0.6	±0.6	±0.6	±0.75	±1.0	1.30	
WDT550-XX-10	DC-10	±0.7	±0.8	±0.8	±1.0	±1.2	1.35	N

※ XX refer to attenuation value in dB



* 外型尺寸公差±5% (Dimensions Tolerance ±5%)

**若非特别说明,外形尺寸和技术指标对应N型连接器(Dimensions and specifications refer to connector type N unless otherwise specified.)

***可按客户要求订制特殊规格衰减量和精度(Custom designs available for other special attenuation value & accuracy.)

俊科[®] SHX 同轴固定衰减器 (Coaxial Fixed Attenuators) 50 ohm

型号(Model Number): DTS60
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 60W
峰值功率(Peak Power): 10KW
(5μs pulse, 6% duty cycle)
外型尺寸(Dimensions):
130×60×60mm
重量(Weight): 510g
温度范围(Tem. Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)						最大驻波比 Max VSWR	连接器形式 Connector Type
		1-9	10	20	30	40			
DTS60-XX-1	DC-1	±0.4	±0.3	±0.3	±0.3	±0.3		1.15	N, SMA, 7/16 , TNC, BNC
DTS60-XX-2	DC-2	±0.5	±0.4	±0.4	±0.5	±0.5		1.20	
DTS60-XX-3	DC-3	±0.6	±0.5	±0.5	±0.6	±0.6		1.30	
DTS60-XX-4	DC-4	±0.75	±0.75	±0.75	±0.75	±0.75		1.35	

※ XX refer to attenuation value in dB



型号(Model Number): DTS60G
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 60W
峰值功率(Peak Power): 5KW
(5μs pulse, 1.2% duty cycle)
外型尺寸(Dimensions):
Ø63×112mm B: Ø30×112mm
重量(Weight): 310g B: 125g
温度范围(Tem. Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)						最大驻波比 Max VSWR	连接器形式 Connector Type
		3/6	10	20	30	40	50		
DTS60G-XX-2.5	DC-2.5	±0.3	±0.3	±0.3	±0.3	±0.3	±0.5	1.10	N, 7/16
DTS60G-XX-4	DC-4	±0.3	±0.3	±0.3	±0.4	±0.5	±0.5	1.15	
DTS60G-XX-6	DC-6	±0.4	±0.4	±0.4	±0.5	±0.75	±0.75	1.20	
DTS60G-XX-8	DC-8	±0.6	±0.6	±0.6	±0.75	±1.0	±1.0	1.30	
DTS60G-XX-10	DC-10	±0.7	±0.8	±0.8	±1.0	±1.2	±1.2	1.35	

※ XX refer to attenuation value in dB



型号(Model Number): DTS80
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 80W
峰值功率(Peak Power): 10KW
(5μs pulse, 0.8% duty cycle)
外型尺寸(Dimensions):
177×98×60mm
重量(Weight): 5Kg
温度范围(Tem. Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40		
DTS80-XX-1-A	DC-1	±0.4	±0.3	±0.3	±0.4	1.15	N, 7/16, TNC, BNC
DTS80-XX-2-A	DC-2	±0.5	±0.4	±0.5	±0.5	1.20	
DTS80-XX-3-A	DC-3	±0.6	±0.5	±0.6	±0.6	1.30	
DTS80-XX-4-A	DC-4	±0.75	±0.75	±0.75	±0.75	1.35	

※ XX refer to attenuation value in dB



型号(Model Number): DTS80G
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 80W
峰值功率(Peak Power): 1KW
(5μs pulse, 8% duty cycle)
外型尺寸(Dimensions):
A: Ø38×199mm B: Ø45×199mm
重量(Weight): A: 270g B: 310g
温度范围(Tem. Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40		
DTS80G-XX-4	DC-4	±1.0	±1.0	±1.0	±1.0	1.25	N, SMA, TNC
DTS80G-XX-8	DC-8	±0.4	±1.0	±1.0	±1.0	1.30	
DTS80G-XX-12.4	DC-12.4	-0.8/+1.5	-0.7/+1.2	-1.0/+1.5	-1.0/+1.5	1.35	
DTS80G-XX-18	DC-18	-1.0/+2.0	±2.0	-1.0/+2.0	-1.0/+2.0	1.40 1.45(SMA)	

※ XX refer to attenuation value in dB



型号(Model Number): WDT80
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 80W
峰值功率(Peak Power): 5KW
(5μs pulse, 1.6% duty cycle)
外型尺寸(Dimensions):
173×76×76mm
重量(Weight): 1.45Kg
温度范围(Tem. Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		3.6	10	20	30	40		
WDT80-XX-2.5	DC-2.5	±0.4	±0.3	±0.3	±0.3	±0.3	1.15	N, 7/16
WDT80-XX-4	DC-4	±0.6	±0.5	±0.5	±0.4	±0.4	1.20	
WDT80-XX-6	DC-6	±0.6	±0.75	±0.75	±0.6	±0.6	1.30	
WDT80-XX-8	DC-8	/	±1.0	±0.75	±0.7	±0.7	1.35	
WDT80-XX-10	DC-10	/	/	/	±0.8	±0.8	1.40	N

※ XX refer to attenuation value in dB



* 外型尺寸公差±5% (Dimensions Tolerance ±5%)

**若非特别说明,外形尺寸和技术指标对应N型连接器(Dimensions and specifications refer to connector type N unless otherwise specified.)

***可按客户要求订制特殊规格衰减量和精度(Custom designs available for other special attenuation value & accuracy.)

俊科[®] SHX 同轴固定衰减器 (Coaxial Fixed Attenuators) 50 ohm

型号(Model Number): DTS100
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 100W
峰值功率(Peak Power): 10KW
(5μs pulse, 1% duty cycle)
外型尺寸(Dimensions):
230×80×60mm
重量(Weight): 1.8Kg
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40-50		
DTS100-XX-1	DC-1	±0.4	±0.4	±0.4	±0.4	1.15	N, 7/16
DTS100-XX-2	DC-2	±0.5	±0.5	±0.5	±0.5	1.20	
DTS100-XX-3	DC-3	±0.6	±0.6	±0.6	±0.6	1.30	
DTS100-XX-4	DC-4	±0.75	±0.75	±0.75	±0.75	1.35	

※ XX refer to attenuation value in dB



型号(Model Number): DTS100-D
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 100W
峰值功率(Peak Power): 5KW
(5μs pulse, 2% duty cycle)
外型尺寸(Dimensions):
A: Ø45×155mm B: Ø63×155mm
重量(Weight): A: 260g B: 450g
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)		最大驻波比 Max VSWR	连接器形式 Connector Type
		30	40		
DTS100-D	DC-4	±0.75		1.25	N, 7/16



型号(Model Number): DDTS100双向(Bi-directional)
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 100W
峰值功率(Peak Power): 5KW
(5μs pulse, 2% duty cycle)
外型尺寸(Dimensions):
205×50×60mm
重量(Weight): 0.83Kg
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)		最大驻波比 Max VSWR	连接器形式 Connector Type
		30	40		
DDTS100-XX-3	0.7-2	±0.6	±0.8	1.15	N
	2-3	±0.6	±0.8	1.20	


※ XX refer to attenuation value in dB



型号(Model Number): WDTs100
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 100W
峰值功率(Peak Power): 5KW
(5μs pulse, 2% duty cycle)
外型尺寸(Dimensions):
A: 173×130×75mm; B: 173×76×76mm
C: 173×78×78mm; E: 68×70×185mm
重量(Weight): A: 1.5Kg B: 1.45Kg
C: 1.5Kg E: 1.12Kg
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		3, 6	10	20	30	40		
WDTs100-XX-2.5	DC-2.5	±0.4	±0.3	±0.3	±0.3	±0.3	1.15	N, 7/16
WDTs100-XX-4	DC-4	±0.6	±0.5	±0.5	±0.5	±0.5	1.20	
WDTs100-XX-6	DC-6	±0.8	±0.75	±0.75	±0.75	±0.75	1.30	N
WDTs100-XX-8	DC-8	±1.0	±0.75	±0.75	±0.75	±0.75	1.35	
WDTs100-XX-10	DC-10	/	/	/	±0.8	±0.8	1.45	

※ XX refer to attenuation value in dB



型号(Model Number): DTS100G(F), DTS100G-A, DTS100G-C
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 100W
峰值功率(Peak Power): 1KW
温度范围(Tem.Range): -55°C~+125°C



型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)							最大驻波比 Max VSWR		连接器形式 Connector Type	外形尺寸 Dimensions (mm)	重量 Weight (g)
									普通型 Normal	精密型 Precise			
		3	6	10	20	30	40	50					
DTS100G(F)-XX-8(E)	DC-8	±1.0	±1.0	-2.0/+1.0	-1.5/+1.0	±1.0	±1.0	±0.5	1.30	1.30	N,TNC, SMA	G:Ø45×253 GF:253×90×100 G-E:253×68×70	G:750 GF:1420 E:1800
DTS100G(F)-XX-12.4(E)	DC-12.4	-1.0/+1.5	-1.0/+3.0	-2.0/+1.5	±1.5	±1.2	±1.2	-0.5/+1.5	1.35	1.35			
DTS100G(F)-XX-18(E)	DC-18	-1.0/+2.0	-1.0/+3.0	-2.0/+2.5	-1.5/+2.5	-1.2/+2.0	-1.2/+2.0	-0.5/+2.0	1.45	1.40			
DTS100G-XX-12.4-A	DC-12.4	-1.0/+1.5	-1.0/+3.0	+1.0/+2.0	+1.0/+2.0	+0.7/-1.0	+0.5/-1.0	-0.5/+1.5	1.35	/	N,TNC, SMA	Ø63×253	780
DTS100G-XX-18-A	DC-18	-1.0/+2.0	-1.0/+3.0	-2.0/+2.5	±2.0	-1.0/+1.5	-1.0/+1.5	-1.0/+1.5	1.45	/			
DTS100G-XX-20-A	DC-20	/	/	/	/	/	-2.0/+1.5	/	1.40	1.35	SMA		
DTS100G-XX-8-C	DC-8	±0.8	±1.0	-2.0/+1.0	-2.0/+1.0	-2.0/+1.0	±1.0	/	1.30	1.20	N,TNC, SMA	308×63×90	950
DTS100G-XX-13-C	DC-13	±1.0	±1.5	-2.0/+1.5	-2.0/+1.5	-2.0/+2.0	±1.2	/	1.35	1.25			
DTS100G-XX-18-C	DC-18	±1.5	±2.0	-2.0/+3.0	/	-2.0/+2.5	±2.0	/	1.40	1.40			

※ XX refer to attenuation value in dB

* 外型尺寸公差±3% (Dimensions Tolerance ±3%)

**若非特别说明,外形尺寸和技术指标对应N型连接器(Dimensions and specifications refer to connector type N unless otherwise specified.)

***可按客户要求订制特殊规格衰减量和精度(Custom designs available for other special attenuation value & accuracy.)

俊科 SHX 同轴固定衰减器 (Coaxial Fixed Attenuators) 50 ohm

型号(Model Number): DTS150
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 150W
峰值功率(Peak Power): 10KW
(5μs pulse, 1.5% duty cycle)
外型尺寸(Dimensions):
230×80×60mm
重量(Weight): 1.8Kg
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40-50		
DTS150-XX-1	DC-1	±0.5	±0.5	±0.5	±0.5	1.15	N,7/16
DTS150-XX-2	DC-2	±1.0	±1.0	±0.8	±0.8	1.20	
DTS150-XX-3	DC-3	±1.5	±1.0	±0.8	±0.8	1.35	
DTS150-XX-4	DC-4	±1.5	±1.5	±1.0	±1.0	1.40	


※ XX refer to attenuation value in dB



型号(Model Number): WDTS150
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 150W
峰值功率(Peak Power): 5KW
(5μs pulse, 3% duty cycle)
外型尺寸(Dimensions):
A:173×130×75mm B:173×78×78mm
E:80×80×185mm
重量(Weight): A:1.5Kg B:1.5Kg
E:1.38Kg
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type	
		3,6	10	20	30			
WDTS150-XX-2.5	DC-2.5	±0.4	±0.3	±0.3	±0.3	1.15	N,7/16	
WDTS150-XX-4	DC-4	±0.6	±0.5	±0.5	±0.5	1.20		
WDTS150-XX-6	DC-6	±0.8	±0.75	±0.75	±0.75	1.30		
WDTS150-XX-8	DC-8	/	±1.0	±0.75	±0.75	1.35		
WDTS150-XX-10	DC-10	/	/	/	±0.8	±0.8	1.45	N

※ XX refer to attenuation value in dB



型号(Model Number): DTS150G(F), DTS150G-A
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 150W
峰值功率(Peak Power): 1KW(5μs pulse, 10% duty cycle)
连接器形式(Connector Type): N, TNC
温度范围(Tem.Range): -55°C~+125°C



型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)							最大驻波比 Max VSWR		外形尺寸 Dimensions (mm)	重量 Weight (g)
									普通型 Normal	精密性 Precise		
		3	6	10	20	30	40	50				
DTS150G(F)-XX-8(-E)	DC-8	-1.0/+0.5	-1.0/+2.5	-2.0/+1.0	-2.0/+1.0	-1.0/+1.5	±1.5	-1.0/+0.75	1.30	1.30	G:Ø45×306	G:0.8
DTS150G(F)-XX-12.4(-E)	DC-12.4	±1.0	-1.0/+2.5	-2.0/+1.0	-2.0/+2.0	-1.0/+1.5	-1.0/+3.0	±1.0	1.40	1.35	GF:306×90×100	GF:1.45
DTS150G(F)-XX-18(-E)	DC-18	-1.0/+2.0	-1.0/+3.5	-2.0/+3.0	-2.0/+3.5	-2.0/+3.5	-2.0/+3.5	±1.5	1.45	1.45	G-E:306×80×80	E:2.5

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)							最大驻波比 Max VSWR		连接器形式 Connector Type	重量 Weight (g)
									普通型 Normal	精密性 Precise		
		3	6	10	20	30	40	50				
DTS150G-XX-6-A	DC-6	±1.0	±0.7	-2.0/+1.0	-1.0/+0.75	-1.0/+0.8	-1.0/+0.8	-1.0/+0.8	1.30	1.25	Ø63×253	0.7
DTS150G-XX-12.4-A	DC-12.4	-1.0/+1.5	-0.7/+3.0	±2.0	±1.0	±1.0	±1.0	±1.0	1.35	1.30		
DTS150G-XX-18-A	DC-18	-1.0/+2.0	-0.7/+3.5	-2.0/+2.5	±2.0	±1.5	±1.5	±1.5	1.45	1.45		

※ XX refer to attenuation value in dB

型号(Model Number): DTS200
特性阻抗(Impedance): 50Ω
平均功率(Average Power): 200W
峰值功率(Peak Power): 10KW
(5μs pulse, 2% duty cycle)
外型尺寸(Dimensions):
267×98×60mm
重量(Weight): 2.8Kg
温度范围(Tem.Range):
-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40-50		
DTS200-XX-1	DC-1	±0.5	±0.5	±0.5	±0.5	1.20	N,7/16
DTS200-XX-2	DC-2	±1.0	±1.0	±0.6	±0.6	1.25	
DTS200-XX-3	DC-3	±1.25	±1.25	±0.8	±0.8	1.35	
DTS200-XX-4	DC-4	±1.5	±1.7	±1.0	±1.0	1.40	

※ XX refer to attenuation value in dB



* 外型尺寸公差±3% (Dimensions Tolerance ±3%)
**若非特别说明,外形尺寸和技术指标对应N型连接器(Dimensions and specifications refer to connector type N unless otherwise specified.)
***可按客户要求订制特殊规格衰减量和精度(Custom designs available for other special attenuation value & accuracy.)

俊科[®] SHX 同轴固定衰减器 (Coaxial Fixed Attenuators) 50 ohm

型号(Model Number): WDTS200

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 200W

峰值功率(Peak Power): 5KW

(5μs pulse, 4% duty cycle)

外型尺寸(Dimensions):

A: 234×130×75mm

B: 234×78×78mm E: 259×80×80mm

重量(Weight): A: 2.2Kg B: 2.3Kg


E: 2.03Kg

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40		
WDTS200-XX-2.5	DC-2.5	±0.8	±0.5	±0.5	±0.5	1.15	N, 7/16
WDTS200-XX-4	DC-4	±1.0	±0.5	±0.5	±0.5	1.25	
WDTS200-XX-6	DC-6	/	±0.6	±0.6	±0.6	1.30	
WDTS200-XX-8	DC-8	/	±0.75	±0.75	±0.75	1.35	
WDTS200-XX-10	DC-10	/	/	±1.0	±1.0	1.45	N

※ XX refer to attenuation value in dB



型号(Model Number): DTS200G(F)

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 200W

峰值功率(Peak Power): 1KW

(5μs pulse, 10% duty cycle)

外型尺寸(Dimensions):

G: 360×63×90mm(with shelf)

GF: 360×108×158mm(with fan)

E: 360×80×80mm

重量(Weight): G: 1.1Kg GF: 2.2Kg

E: 3Kg

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40	50		
DTS200G(F)-XX-8(E)	DC-8	-2.5±1.0	-2.5±1.5	±1.5	±1.5	±1.5	1.25	N, TNC
DTS200G(F)-XX-12.4(E)	DC-12.4	-2.5±1.0	-2.5±1.5	-1.5±2.0	-1.0±3.0	-1.5±2.5	1.40	
DTS200G(F)-XX-18(E)	DC-18	-2.5±1.0	-2.5±1.5	-2.0±3.5	-2.0±3.5	-2.0±3.0	1.50	

※ XX refer to attenuation value in dB



型号(Model Number): DTS250

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 250W

峰值功率(Peak Power): 10KW

(5μs pulse, 2.5% duty cycle)

外型尺寸(Dimensions):

267×98×60mm

重量(Weight): 2.8Kg

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40-50		
DTS250-XX-1	DC-1	±0.5	±0.5	±0.5	±0.5	1.20	N, 7/16
DTS250-XX-2	DC-2	±1.0	±1.0	±0.75	±0.75	1.25	
DTS250-XX-3	DC-3	±1.25	±1.25	±1.0	±1.0	1.35	
DTS250-XX-4	DC-4	±1.5	±1.5	±1.0	±1.0	1.40	

※ XX refer to attenuation value in dB



型号(Model Number): DTS250-B

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 250W

峰值功率(Peak Power): 5KW

(5μs pulse, 5% duty cycle)

外型尺寸(Dimensions):

234×78×78mm

重量(Weight): 1.8Kg

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)		最大驻波比 Max VSWR	连接器形式 Connector Type
		40			
DTS250-XX-1.5-B	DC-1.5	±0.5		1.15	N,7/16
DTS250-XX-3-B	DC-3	±0.5		1.15	
DTS250-XX-4-B	DC-4	±0.5		1.15	
DTS250-XX-6-B	DC-6	±0.5		1.15	

※ XX refer to attenuation value in dB



型号(Model Number): WDTS250

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 250W

峰值功率(Peak Power): 5KW

(5μs pulse, 5% duty cycle)

外型尺寸(Dimensions):

A: 234×130×75mm

C: 234×78×78mm; E: 259×80×80mm

重量(Weight): A: 2.2Kg C: 2.3Kg


E: 2.03Kg

温度范围(Tem.Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40		
WDTS250-XX-2.5	DC-2.5	±0.8	±0.5	±0.5	±0.5	1.20	N, 7/16
WDTS250-XX-4	DC-4	±1.0	±0.5	±0.5	±0.5	1.25	
WDTS250-XX-6	DC-6	/	±0.6	±0.6	±0.6	1.30	
WDTS250-XX-8	DC-8	/	±0.75	±0.75	±0.75	1.35	
WDTS250-XX-10	DC-10	/	/	±1.0	±1.0	1.45	N

※ XX refer to attenuation value in dB



* 外型尺寸公差±5% (Dimensions Tolerance ±5%)

**若非特别说明,外形尺寸和技术指标对应N型连接器(Dimensions and specifications refer to connector type N unless otherwise specified.)

***可按客户要求订制特殊规格衰减量和精度(Custom designs available for other special attenuation value & accuracy.)

俊科 SHX 同轴固定衰减器 (Coaxial Fixed Attenuators) 50 ohm

型号(Model Number): DTS250G(F)

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 250W

峰值功率(Peak Power): 1KW

(5μs pulse, 10% duty cycle)

外型尺寸(Dimensions):

G: 360×63×90mm(with shelf)

GF: 360×108×158mm(with fan)

E: 360×80×80mm

重量(Weight): G: 1.1Kg GF: 2.2Kg

E: 3Kg

温度范围(Tem. Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR		连接器形式 Connector Type
		10	20	30	40	50	普通型 Normal	精密型 Precise	
DTS250G(F)-XX-8(E)	DC-8	±1.5	-2.0/+1.5	±1.5	±1.5	±1.5	1.30	1.25	N,TNC
DTS250G(F)-XX-12.4(E)	DC-12.4	-1.5/+2.0	-2.5/+1.0	±2.0	±2.0	±2.0	1.40	1.30	
DTS250G(F)-XX-18(E)	DC-18	-2.5/+4.0	-2.5/+5.0	-2.0/+3.5	-2.0/+3.5	-2.0/+3.0	1.55	1.50	

※ XX refer to attenuation value in dB



型号(Model Number): DTS300

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 300W

峰值功率(Peak Power): 10KW

(5μs pulse, 3% duty cycle)

外型尺寸(Dimensions):

A: 327×98×60mm

B: 353×140×132mm


重量(Weight): A: 3Kg B: 7.3Kg

温度范围(Tem. Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40-50		
DTS300-XX-1	DC-1	±1.0	±1.0	±0.75	±0.75	1.20	N,7/16
DTS300-XX-2	DC-2	±1.5	±1.5	±1.0	±1.0	1.25	
DTS300-XX-3	DC-3	±1.75	±1.75	±1.25	±1.25	1.35	
DTS300-XX-4	DC-4	±2.0	±2.0	±1.5	±1.5	1.50	

※ XX refer to attenuation value in dB



型号(Model Number): WDTS300

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 300W

峰值功率(Peak Power): 5KW

(5μs pulse, 6% duty cycle)

外型尺寸(Dimensions):

295×130×75mm;

AF: 295×130×177mm

重量(Weight): 3.5Kg; (AF) 4Kg

温度范围(Tem. Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)				最大驻波比 Max VSWR	连接器形式 Connector Type
		10	20	30	40-50		
WDTS300-XX-4	DC-4	/	/	±0.5	±0.5	1.25	N,7/16
WDTS300-XX-6	DC-6	/	/	±0.75	±0.75	1.30	
WDTS300-XX-8	DC-8	/	/	±1.0	±1.0	1.40	
WDTS300-XX-10	DC-10	/	/	±1.0	±1.0	1.45	

※ XX refer to attenuation value in dB



型号(Model Number): DTS300GH(F)

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 300W

峰值功率(Peak Power): 1KW

(5μs pulse, 10% duty cycle)

外型尺寸(Dimensions):

GH: 468×63×92mm

GHF: 468×108×153mm

E: 468×80×80mm

重量(Weight): GH: 1.5Kg; GHF: 2.85Kg

E: 4Kg


温度范围(Tem. Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减値及精度 Attenuation Value & Accuracy(dB)			最大驻波比 Max VSWR		连接器形式 Connector Type
		10	20	30	普通型 Normal	精密型 Precise	
DTS300GH(F)-XX-8(E)	DC-8	-3.0/-1.5	-3.5/-1.5	-3.0/-1.5	1.35	1.30	N
DTS300GH(F)-XX-12.4(E)	DC-12.4	-3.0/-1.5	-3.5/-1.5	-3.0/+2.0	1.45	1.45	
DTS300GH(F)-XX-18(E)	DC-18	±3.0	-3.5/+5.0	-3.0/+3.5	1.50	1.50	

型号 Model Number	频率范围 Frequency Range(GHz)	衰减値及精度 Attenuation Value & Accuracy(dB)		最大驻波比 Max VSWR		连接器形式 Connector Type
		40	50	普通型 Normal	精密型 Precise	
DTS300GH(F)-XX-8(E)	DC-8	±1.5	±1.5	1.35	1.30	N
DTS300GH(F)-XX-12.4(E)	DC-12.4	-1.5/+2.0	-1.5/+2.0	1.45	1.45	
DTS300GH(F)-XX-18(E)	DC-18	-2.0/+3.0	-2.0/+3.0	1.50	1.50	

※ XX refer to attenuation value in dB



型号(Model Number): DTS350G(F)

特性阻抗(Impedance): 50Ω

平均功率(Average Power): 350W

峰值功率(Peak Power): 1KW

(5μs pulse, 10% duty cycle)

外型尺寸(Dimensions):

GH: 468×63×92mm

GHF: 468×108×153mm

E: 468×80×80mm

重量(Weight): GH: 1.5Kg; GHF: 2.85Kg


E: 4Kg

温度范围(Tem. Range):

-55°C~+125°C

型号 Model Number	频率范围 Frequency Range(GHz)	衰减值及精度 Attenuation Value & Accuracy(dB)					最大驻波比 Max VSWR	连接器形式 Connector Type
		6	10	20	30	40		
DTS350G(F)-XX-4(E)	DC-4	-0.8/+1.5	-0.5/+1.0	±1.0	-1.0/+0.5	±1.0	1.30	N(J,K)
DTS350G(F)-XX-8(E)	DC-8	±1.5	-1.5/+2.5	±1.5	±1.0	±1.0	1.35	
DTS350G(F)-XX-12.4(E)	DC-12.4	±1.5	-1.5/+4.0	-1.5/+3.5	±2.0	±2.0	1.45	
DTS350G(F)-XX-13(E)	DC-13	-1.5/+2.5	-1.5/+4.0	-1.5/+5.0	±2.0	±2.0	1.50	

※ XX refer to attenuation value in dB



* 外型尺寸公差±5% (Dimensions Tolerance ±5%)

**若非特别说明,外形尺寸和技术指标对应N型连接器(Dimensions and specifications refer to connector type N unless otherwise specified.)

***可按客户要求订制特殊规格衰减量和精度(Custom designs available for other special attenuation value & accuracy.)